

# PRIMER COAT SCG 360



## DESCRIPTION

Primer coat SCG 360 is a cold applied, general purpose roofing primer formulated with highly pliable, flexible bitumen, water based and compounded with wetting and saturation additives.

## USES

Primer coat SCG 360 is suitable for concrete, smooth asphalt roofs, brick and metal surfaces, used as the prime coat prior to installation of any bitumat membrane. Select solvent allows for optimum penetration of Bitumat concrete primer into the surface pores, pinhole sand cracks. Absorbs the existing dust and scale thus the resulting surface permits the proper bonding of self-adhesive as well as torchable membranes, in addition to any other bituminous adhesives and coatings.

## APPLICATION

The surface must be thoroughly cleaned, and all dust, dirt, loose coatings, oil or greasy substances removed. Concrete must be completely cured and dried prior to priming. Primer coat SCG 360 should be allowed to dry before application of subsequent coat/membrane. It can be applied with a roofing brush, roller, squeegee, or airless spray equipment at the recommended coverage rate

## COVERAGE RATE

0.2 - 0.4 kg/m<sup>2</sup>, depending on condition of substrate.

## STANDARD TEST

ASTM D5, ASTM D244 & NF T 66-016

## PACKING

20 kg per-pail and 200 kg per-drums.

## HEALTH AND SAFETY

Wear protective clothing, gloves and goggles during application.

1. Fire - no-flammable when wet because mix of water based content.
2. Gloves and goggles should be worn. Any splashes to the skin or eyes should be washed off with clean water.
3. Skin - Avoid repeated or prolonged contact. However, if it occurs, remove with hand cleaner that removes oil or grease, then clean with soap and water.
4. Eyes - Contact could cause irritation. If contact occurs, flush immediately with clean Water.

## CLEANING

Tools :

Clean with kerosene.

Hands :

Use a hand cleaner or kerosene followed by soap and water.



**PT. SELARAS CIPTA GLOBAL**

Taman Kebon Jeruk Blok AA IV No: 12, Jalan Meruya Ilir Raya, Jakarta Barat - 11650  
Phone : (021) 5853295 - 5857441 - Fax : (021) 5853267  
Email : selarasglobal@yahoo.com - Website : <http://www.selarascipta.com>